




EWIND Cloud-Managed AI PoE Switch

EW-ES2006CFSH-AP | EW-ES2010CFSH-AP | EW-ES2020CFSH-AP | EW-ES2028CFSH-AP



**Visual
Topology**



**Remote
Easy Maintenance**



**Port Auto
Detection**



**Real-time
Alarm Notification**




**Watchdog
Function**



**Extend
300meter**


The EWIND Cloud-managed PoE Switch Series features an advanced remote online management platform designed to deliver quick responses and versatile capabilities. Key features include PoE scheduling, Watchdog (PoE auto-alive check), Extend 300M, port settings, alarm notifications, VLAN configuration, and topology mapping etc. These functionalities enable users to manage their networks with ease, ensuring optimal performance, enhanced productivity, and an improved user experience. With the EWIND Cloud App/Website Platform, users can monitor and maintain their network and security systems anytime, anywhere.



Key features



- Support PoE Watchdog / VLAN / Extend 300meters via a DIP-switch;
- Supports EWIND remote cloud platform management and mobile app operation, offering various real-time alerts notifications, fault detection and port reset etc;
- Discovers devices using the ONVIF protocol to display a cloud-based topology map of connected PDs;
- Support IEEE802.3af/at/bt PoE++ Standard, PoE Power up to 90W for specify ports;

Technical Specifications




Model	EW-ES2006CFSSH-AP	EW-ES2010CFSSH-AP	EW-ES2020CFSSH-AP	EW-ES2028CFSSH-AP
PoE+ Ports	4*10/100Mbps	8*10/100Mbps	16*10/100Mbps	24*10/100Mbps
PoE++ 90W Ports	Port 4 (60W/90W)	Port 7-8	Port 13-16	Port 21-24
Uplink Ports	2*10/100Mbps RJ45 Ports	2*10/100Mbps RJ45 Ports	2*10/100/1000Mbp RJ45 Ports 2*100/1000Mbps SFP Fiber Ports	2*10/100/1000Mbps RJ45 Ports 2*100/1000Mbps SFP Fiber Ports
Switching Capacity	1.2Gbps	2Gbps	11.2Gbps	12.8Gbps
Forwarding Rate	0.893Mpps	1.488Mpps	2.976Mpps	4.166Mpps
MAC Address Table	2K	2K	8K	8K
Buffer Memory	2M	2M	2M	2M
Power Supply	65W (100-240V)	120W(100-240V)	250W(100-240V)	300W(100-240V)
Power Consumption	Standby:<2W; Full load:<65W.	Standby:<2W; Full load:<120W.	Standby:<5W; Full load:<250W.	Standby:<5W; Full load:<300W.
PoE Standard	Port 1-4 support @IEEE802.3af/at; Port 4 support @IEEE802.3af/at/BT (Max. 60W/port)	Port 1-8 support @IEEE802.3af/at; Port 7-8 support @IEEE802.3af/at/BT (Max. 90W/port).	Port 1-16 support @IEEE802.3af/at; Port 13-16 support @IEEE802.3af/at/BT (Max. 90W/port).	Port 1-24 support @IEEE802.3af/at; Port 21-24 support @IEEE802.3af/at/BT (Max. 90W/port).
Network Protocol	IEEE802.3 10BASE-T; IEEE802.3i 10Base-T; IEEE802.3x; IEEE802.3u 100Base-TX; IEEE802.3ab 1000Base-T.		IEEE802.3 10BASE-T; IEEE802.3i 10Base-T;IEEE802.3x; IEEE802.3u 100Base-T;IEEE802.3ab 1000Base-T; IEEE802.3z 1000base-X;IEEE802.3u 100Base-FX;	
Power Supply Pin	Default 1/2(+), 3/6(-).			
Power Supply	Built-in power supply AC100~240V 50-60Hz.			
Dimension	125*115*33mm	195*130*40mm	330*215*44mm	330*215*44mm
Net /Gross Weight	<0.5kg / <0.8kg	<0.8kg / <1.2kg	<2.5kg / <3kg	<2.5kg / <3kg

Technical Specifications




Model	EW-ES2006CFSSH-AP	EW-ES2010CFSSH-AP	EW-ES2020CFSSH-AP	EW-ES2028CFSSH-AP
DIP-Switch Function	With the Dial code switch, support port priority by default. 1: AI Extend 300meters transmission and auto speed change of single port (limit 10Mbps), other ports maintain 1000M within 100 meters; 2: Turn on, Each Port support each port Isolation & VLAN; 3: Turn on, Each Port support AI-PoE Network self-healing mode (PoE Watchdog function), Automatic solve the camera problem & reduce after-sale.			
Operation TEMP / Humidity	-20~+55°C;5%~90% RH non condensing			
Storage TEMP / Humidity	-40~+75°C;5%~95% RH non condensing			
Installation Method	Desktop type, wall mounted;		Desktop, rack mounted	
Protection	IEC61000-4-2(ESD): ±8kV contact discharge, ±15kV air discharge; IEC61000-4-5(Lightning protection/Surge): Power:CM±4kV/DM±2kV; Port: ±4kV.			
Protection Level	IP30			
Certification	CCC; CE mark,commercial;CE/LVD EN60950; FCC Part 15 Class B; RoHS.			
Warranty	3 years, lifetime maintenance.			


Appearances and Dimensions




EW-ES2006CFSSH-AP



EW-ES2010CFSSH-AP



EW-ES2020CFSSH-AP



EW-ES2028CFSSH-AP

Packing list

CONTENT	QTY	UNIT
Megabit Cloud-Managed AI PoE Switch	1	SET
AC Power Cord	1	PC
User Guide and Warranty Card	1	PC
Hanging Ear (EW-ES2020CFSSH (ES2028CFSSH) -AP)	1	PAIR

Contact us

EWIND Technology Co., Limited.

Office Address: Room 508, 5/F, XingHe World Tower E, Yabao Road, Longhua Dist, Shenzhen City, Guangdong, China.
 Factory Address: 5th floor, Building 3, ZhongYuntai industrial area, Songbai Road, Shiyan Street, Bao'an District, Shenzhen China.
 Email: info@ewindnet.com
 Tel: +86-755-2100 6440

